



product datasheet

heating & ventilation

tek screw



TSHV4.2-12-1



TSHV4.8-15-1

Designed for:	Assembly and fabrication of ducting and air conditioning systems.
Head Style:	Hexagonal
Drive Bit:	5/16" Hexagonal
Thread Form:	Twin
Drill Point:	Tek 1
Shank Material:	Carbon steel
Material Grade:	AISI C1022
Coating:	Electroplated zinc
Steel Thickness:	0.8mm - 2.5mm
Recommended Drill Speed:	2,000 - 3,000 RPM

Evolution Fasteners (UK) Ltd
 Unit 4, Block 16
 Clydesmill Road
 Clydesmill Industrial Estate
 Glasgow
 G32 8RE
 Tel: +44(0)141 646 0055
 Fax: +44(0)141 646 0033
 technical@evolutionfasteners.co.uk

Heating and Ventilation Tek Screw Range				
Product Code	Size	Box Qty	Carton Qty	Effective Thread Length
TSHV4.2-12-1	4.2 x 12mm	1,000	10,000	8mm
TSHV4.8-15-1	4.8 x 15mm	1,000	10,000	10mm

Ultimate Mechanical Performance		
Diameter	Tensile Strength	Shear Strength
4.2mm	1.4kN	0.8kN
4.8mm	1.6kN	0.9kN

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets