


# product datasheet

## steel ceiling anchor



www.evolutionfasteners.co.uk



<b>Designed for:</b>	Use with angle brackets in concrete ceilings where regulations dictate all steel anchors should be used for overhead fixings.
<b>Head Style:</b>	Flat
<b>Coating:</b>	Yellow zinc passivated
<b>Shank Material:</b>	Carbon steel
<b>Material Grade:</b>	AISI C1022
<b>Drill Diameter:</b>	6mm
<b>Pilot Hole:</b>	6mm
<b>Min. Drill Depth:</b>	30.0mm
<b>Fixture Thickness:</b>	5mm
<b>Fire Tested:</b>	Yes, to EN1364-1 (ask for details of our fire test results for more information)

Evolution Fasteners (UK) Ltd  
 Unit 4, Block 16  
 Clydesmill Road  
 Clydesmill Industrial Estate  
 Glasgow  
 G32 8RE  
 Tel: +44(0)141 646 0055  
 Fax: +44(0)141 646 0033  
 technical@evolutionfasteners.co.uk

Steel Metal Nail in Anchor Range			
Product Code	Size	Box Qty	Carton Qty
EVDBZ640	M6 x 40mm	100	2,000
EVDBZ665	M6 x 65mm	100	1,500

Recommended Working Loads		
Product Code	Ultimate Load	
	C20/25 Concrete	Solid Brick
EVDBZ640	7.5kN	6.0kN
EVDBZ665	7.5kN	6.0kN

### Application Guide

1. Drill 6mm diameter hole at a depth of anchor plus 5mm
2. Clean out drill hole
3. Insert anchor through fixing
4. Set anchor using a hammer by driving the nail until it has become flush with anchor collar

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets