

product datasheet

wirehanger



www.evolutionfasteners.co.uk



Designed for:	Fixing cables/wires in suspended ceiling apps.
Product Code:	WH6
Size:	M6 x 60mm
Head Style:	Flat
Eye Diameter:	6.5mm
Coating:	Clear zinc passivated
Shank Material:	Carbon steel
Material Grade:	AISI C1022
Drill Diameter:	6mm
Pilot Hole:	6mm
Min. Drill Depth:	35.0mm
Fire Tested:	Yes, to EN1364-1 (ask for details of our fire test results for more information)
Box Qty:	100
Carton Qty:	2,000

Evolution Fasteners (UK) Ltd
 Unit 4, Block 16
 Clydesmill Road
 Clydesmill Industrial Estate
 Glasgow
 G32 8RE
 Tel: +44(0)141 646 0055
 Fax: +44(0)141 646 0033
 technical@evolutionfasteners.co.uk

Application Guide

1. Drill 6mm diameter hole a minimum of 35mm deep
2. Clean out drill hole
3. Position anchor in hole, tap in until it can go no further
4. Attach wire to eye and pull to set

Recommended Working Load in C30/37 Concrete

Recommended Load: 1.0kN
 Ultimate Load: 4.5kN

Ask for Evolution



Drywall Screws



Tek Screws



Collated Screws



Masonry Screws



Anchors



Clips & Brackets