




product datasheet

drop in anchors



Designed for:	Fixing bolts/threaded rod to concrete in heavy duty applications (setting tool required).
Coating:	Electroplated Zinc
Material:	Carbon steel
Material Grade:	AISI C1022

Evolution Fasteners (UK) Ltd
 Unit 4, Block 16
 Clydesmill Road
 Clydesmill Industrial Estate
 Glasgow
 G32 8RE
 Tel: +44(0)141 646 0055
 Fax: +44(0)141 646 0033
 technical@evolutionfasteners.co.uk

Drop in Anchors Range					
Product Code	Size	Box Qty	Carton Qty	Min. Drill Depth	Pilot Hole
EADI625	6mm x 25mm	100	2,000	25mm	8mm
EADI830	8mm x 30mm	100	2,000	30mm	10mm
EADI1040	10mm x 40mm	100	1,000	40mm	12mm

Ultimate Pull Out Values		
Diameter	Aerated Concrete Block	C35/40 Concrete
6mm	0.5kN	0.9kN
8mm	1.4kN	2.1kN
10mm	2.8kN	4.2kN

Spacing Information			
Diameter	Min. Concrete Thickness	Min. Spacing (centre to centre)	Min. Distance from Edge of Concrete
6mm	100mm	60mm	110mm
8mm	100mm	60mm	110mm
10mm	100mm	80mm	140mm

- ### Application Guide
1. Drill appropriately sized pilot hole
 2. Clean out drill hole
 3. Set anchor using appropriate setting tool
 4. Insert bolt or rod and tighten

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets