

product datasheet

stainless steel

stitching tek screws



www.evolutionfasteners.co.uk



SSH4.8-16-3



SSPH5.5-19-3



SSS6.3-22-2

Designed for:	Assembly/fabrication of heating, ducting and ventilation systems (SSH4.8-16-3) Fixing steel to steel (SSPH5.5-19-3) Stiching cladding panels (SSS6.3-22-2)
Washer on SSS6.3-22-2:	16mm Ø bonded EPDM
Thread Form:	Twin
Shank Material:	Stainless steel
Material Grade:	AISI A410
Recommended Drill Speed:	1,500 - 2,500 RPM

Evolution Fasteners (UK) Ltd
Unit 4, Block 16
Clydesmill Road
Clydesmill Industrial Estate
Glasgow
G32 8RE
Tel: +44(0)141 646 0055
Fax: +44(0)141 646 0033
technical@evolutionfasteners.co.uk

Stainless Steel Stitching Tek Screw Range								
Product Code	Size	Box Qty	Carton Qty	Head Style	Drive Bit	Drill Point	Effective Thread Length	Drilling Capacity
SSH4.8-16-3	4.8 x 16mm	1,000	10,000	Hexagonal	5/16" Hexagonal	Tek 3	10mm	1.2 - 3.5mm
SSPH5.5-19-3	5.5 x 19mm	200	5,000	Pancake	Phillips 3	Tek 2	14mm	1.2 - 3.5mm
SSS6.3-22-2	6.3 x 22mm	100	8,000	Hexagonal	5/16" Hexagonal	Tek 2	15mm	0.8 - 2.5mm

Ultimate Mechanical Performance		
Diameter	Tensile Strength	Shear Strength
4.8mm	3.6kN	2.6kN
5.5mm	5.7kN	3.7kN
6.3mm	7.4kN	4.7kN

Ask for Evolution



Drywall Screws



Tek Screws




Collated Screws



Masonry Screws



Anchors



Clips & Brackets