

product datasheet

collated coarse thread drywall screw (phosphate)



www.evolutionfasteners.co.uk



Fine thread screws have diminished holding power as wood dries.



Evolution coarse thread drywall screws have fewer threads so require fewer revolutions meaning faster installation. They also have deeper threads for superior holding power.

Fibres are pulled up during installation. As wood dries the natural tendency of wood fibres is to spring back to their original position. Wood pulls the screws inwards, eliminating 'head pops'.

Evolution Fasteners (UK) Ltd
Unit 4, Block 16
Clydesmill Road
Clydesmill Industrial Estate
Glasgow
G32 8RE
Tel: +44(0)141 646 0055
Fax: +44(0)141 646 0033
technical@evolutionfasteners.co.uk

Designed for:	Fixing plasterboard to timber studs.
Head Style:	Bugle
Drive Bit:	Phillips 2
Drill Point:	Super sharp point
Thread Form:	Single thread, fine
Coating:	Black phosphate
Shank Material:	Carbon steel
Material Grade:	AISI C1022
Effective Thread Length:	Fully threaded
Recommended Drill Speed:	2,000 - 3,000 RPM
Steel Thickness:	0.5mm - 1.0mm

Collated Coarse Phosphate Drywall Range

Product Code	Size	Box Qty	Carton Qty	Fixture Thickness
CDWCP25	3.5mm x 25mm	1,000	10,000	8mm
CDWCP32	3.5mm x 32mm	1,000	10,000	12mm
CDWCP35	3.5mm x 35mm	1,000	10,000	15mm
CDWCP38	3.5mm x 38mm	1,000	10,000	18mm
CDWCP42	3.5mm x 42mm	1,000	10,000	20mm
CDWCP45	3.5mm x 45mm	1,000	10,000	22mm
CDWCP50	3.5mm x 50mm	1,000	10,000	25mm
CDWFZ55	3.5mm x 55mm	1,000	10,000	30mm
CDWFZ65	4.2mm x 65mm	500	5,000	45mm
CDWFZ75	4.2mm x 75mm	500	5,000	55mm

Ask for Evolution



Drywall Screws



Tek Screws



Collated Screws



Masonry Screws



Anchors



Clips & Brackets