



PRODUCT DATASHEET

FIBROUS CEMENT BOARD SCREW

PRODUCT DETAILS

Purpose:	Fixing fibrous cement sheets to timber
Head style:	Hexagonal
Drive Bit:	5/16" Hexagonal
Drill Point:	Gash point
Thread Form:	Single
Coating:	Electroplated Zinc
Shank Material:	Stainless Steel
Material Grade:	EN 1.4301/ A2 (AISI 304)
Drilling Point Material Grade:	EN 1.4301/ A2 (AISI 304)
Recommended Drill Speed:	1,500 - 2,500 RPM
Washer:	Baz washer

GENERAL PHYSICAL CHARACTERISTICS

SKU	Nominal Dimensions, $d_{nom} \times L_{nom}$ (mm)	Effective Thread Length (mm)
A2SSDH6.3-130-GP	6.3 x 130.0	50.0

CHARACTERISTIC PULL OUT VALUES

Nom. Dia. (mm)		Timber Embedment Depth (mm)	
		25	35
6.3	Type 17	2,860N	4,537N

CHARACTERISTIC MECHANICAL PROPERTIES

	Magnitude
Tensile capacity _{s(F_{ult,Rk})}	10,276N
Shear capacity _{s(V_{ult,Rk})}	6,972N
Torque _{s(τ_{ult,Rk})}	9.0Nm

NOTE: The results expressed in this document are determined from empirical testing. Specifiers, end-users and other third parties should make their own decision(s) on what safety factors to use relevant to their design(s)/ application(s). This document is provided, strictly: without prejudice, without recourse, without liability, non-assumpsit, no assured value, errors and omissions excepted, subject to change without notice and all rights reserved.
©Evolution Fasteners UK Ltd, 2021.