Evolution Fasteners (UK) Ltd Units 2A & 2B Clyde Gateway Trade Park Dalmarnock Road, Rutherglen, Glasgow G73 1AN

Tel: +44 (0)141 647 7100 Fax: +44 (0)141 647 5100 Email: technical@evofas.com











Bi-Metal Composite Panel Fastener Range - Products for use in Heavy Gauge Applications (4.0mm to 12.5mm mild steel)

FASTENER

Product Code	Size	Washer	Insulation Thickness Range	Drilling Capacity
BMTSBWHT5.5-105-5	5.5 x 105mm	16mm	50mm-65mm	4.0 - 12.5mm
BMTSBWHT5.5-125-5	5.5 x 125mm	16mm	50mm-85mm	4.0 - 12.5mm
BMTSBWHT5.5-150-5	5.5 x 150mm	16mm	75mm-110mm	4.0 - 12.5mm
BMTSBWHT12-5.5-185-5	5.5 x 185mm	12mm	110mm-145mm	4.0 - 12.5mm
BMTSBWHT16-5.5-185-5	5.5 x 185mm	16mm	110mm-145mm	4.0 - 12.5mm
BMTSBWHT-5.5-185-5	5.5 x 185mm	19mm	110mm-145mm	4.0 - 12.5mm
BMTSBWHT12-5.5-245-5	5.5 x 245mm	12mm	170mm-205mm	4.0 - 12.5mm
BMTSBWHT16-5.5-245-5	5.5 x 245mm	16mm	170mm-205mm	4.0 - 12.5mm
BMTSBWHT5.5-245-5	5.5 x 245mm	19mm	170mm-205mm	4.0 - 12.5mm

Technical Data							
Tek 5 range – unfactored pull out values							
	Steel Thickness						
Diameter	meter Drill Point	4.0mm	5.0mm	6.0mm	8.0mm	10.0mm	12.5mm
5.5mm	Tek 5	6.4kN	7.7kN	10.1kN	11.4kN	12.3kN	12.8kN

Pullover Performance				
Diameter	In 0.6mm steel	In 1.2mm steel		
5.5mm	2.4kN	8.1kN		

Offimate Mechanical Performance				
Diameter	Tensile Strength	Shear Strength		
5.5mm	13.3kN	9.9kN		

NOTE: The results expressed in this document are determined from empirical testing. Specifiers, end-users and other third parties should make their own decision(s) on what safety factors to use relevant to their design(s)/ application(s). This document is provided, strictly: without prejudice, without recourse, without liability, non-assured value, errors and omissions excepted, subject to change without notice and all rights reserved.

© Evolution Fasteners UK Ltd, 2021.